



Technical Data Sheet

Pres-On PBTP-67 Permanent Bag Sealing Tape

- For use in sealing paper and plastic envelopes
- Transfer tape on unsupported adhesive
- Rubber based hot melt adhesive
- Designed to distort and tear film up to 3 mils
- Available on rolls up to 3000 feet

GENERAL DESCRIPTION

Pres-On PBTP-67 is a transfer tape with an unsupported adhesive that is designed to distort and tear film up to 3 Mils (75 microns) thick.

APPLICATIONS

PBTP-67 is used as an aggressive adhesive for the permanent sealing of paper and plastic envelopes. Low slip or no slip films are recommended. A Corona treatment will improve adhesion. In application to plastic films, the manufacturer is required to have cold knife cutting capabilities to cut the tape.

STANDARD ROLL SIZES

SERIAL NUMBER	ADHESIVE WIDTH	LINER WIDTH	ROLL LENGTH
PBTP67	5/16" (8 mm)	1/2" (12 mil)	3000 feet
PBTP67	1/2" (12 mm)	3/4" (19 mil)	3000 feet
PBTP67	1/2" (12 mm) or 3/4" (19 mm)	1" (25 mil)	3000 feet

PROPERTIES

SPECIFICATION	
Thickness	1.0 mil (43 microns)
Release Liner	42 lb printed bleached kraft paper
Color	Clear
Adhesive	Rubber Based Hot Melt Adhesive
Adhesion	2700 gm/in (6.0 #/in)

APPLICATION NOTES

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.