



Technical Data Sheet

Shur-Step™ Abrasive Anti-Slip Material

- Anti-Slip material stabilizes dangerous, slippery areas
- Versatile for application on lawn tractors, vehicles, stairs, food service indoor/outdoor areas and more
- Adhesive system bonds to powder-coated paint and raw concrete
- Available in Heavy Duty (60 grit) and General Purpose (80 grit)
- Available in standard size rolls and cleats, plus can be custom ordered in non-standard die-cut shapes and non-standard rolls

GENERAL DESCRIPTION

Shur-Step

Low profile, high-strength and water resistant, Shur-Step tape features a self-adhesive backing that applies in seconds and adheres to any smooth, clean, dry surface. Finely ground abrasive particulates provide a sturdy footing, indoors or outdoors.

APPLICATIONS

Provides maximum skid resistance on a wide variety of floor types and surfaces, including the powder coated paint finishes found on lawnmowers, truck beds, snowmobiles and other commercial products. Ideal safety solution in factories or warehouses when applied to steps, ramps, loading docks, ladders, around machinery or anywhere slippery conditions exist.

STANDARD ROLL SIZES



SERIAL NUMBER	THICKNESS	WIDTH	LENGTH
General Purpose GP (80 grit)			
	0.025	3/4 inch	60 feet
	0.025	1 inch	60 feet
	0.025	2 inch	60 feet
	0.025	4 inch	60 feet
	0.025	8 inch	60 feet
	0.025	12 inch	60 feet
	0.025	24 inch	60 feet
Heavy Duty HD (60 grit)			
	0.032	3/4 inch	60 feet
	0.032	1 inch	60 feet
	0.032	2 inch	60 feet
	0.032	4 inch	60 feet
	0.032	8 inch	60 feet
	0.032	12 inch	60 feet
	0.032	24 inch	60 feet
Cleats			
	0.025	3/4 inch	24 inch
	0.025	6 inch	24 inch
	0.032	3/4 inch	24 inch
	0.032	6 inch	24 inch

PHYSICAL PROPERTIES**PROPERTY**

Backing	3 mil Polyethylene
Prime Coat	Resin Binder
Abrasive	Silicone Carbide
Top Coat	Resin Binder
Adhesive	Hot Melt Rubber
Color	Black
Liner	54 lbs Brown Kraft 3.2 mil thick, 2-Side
Thickness (General Purpose)	0.025
Thickness (Heavy Duty)	0.032

1. This information is furnished as a guide for selecting materials. Pres-On disclaims liability for results or use of this information. It is the customer's responsibility to obtain and test samples when determining suitability of material for a particular application.
2. Information and specifications are based upon research and believed to be true but do not constitute a warranty. Pres-On products are sold with the understanding that the purchaser will determine the suitability of the materials for their purpose. Pres-On will supply samples for your testing and evaluation.

APPLICATION NOTES

Thoroughly clean contact surface before use. Once tape has been applied, it cannot be removed and reused. Therefore, position tape carefully, assuring that it is in contact with all surfaces. If tape is misaligned, remove used unit, discard and repeat application with new unit. Test product for system compatibility as individual application conditions can impact results. Pres-On does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.